

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5






FIG. 7





FIG. 8






FIG. 11




FIG. 12

13/29




FIG. 13

FIG. 16




FIG. 15




FIG. 17





FIG. 14 Prior Art






FIG. 18

Boiling Heat Transfer Predictions

70 °F Ambient Input: $C_{SF} = 0.0058$ (Teflon Coated Stainless)




Fig. 19

Boiling Heat Transfer Predictions

70 °F Ambient Input: $C_{SF} = 0.0080$ (Ground Polished Stainless)




Fig. 20

Boiling Heat Transfer Predictions

90 °F Ambient Input: $C_{SF} = 0.0058$ (Teflon Coated Stainless)




Fig. 21

Boiling Heat Transfer Predictions

90 °F Ambient Input: $C_{sf} = 0.0080$ (Ground Polished Stainless)




Fig. 22

Boiling Heat Transfer Predictions

110 °F Ambient Input: $C_{SF} = 0.0058$ (Teflon Coated Stainless)




Fig. 23

Boiling Heat Transfer Predictions

110 °F Ambient Input: $C_{SF} = 0.0080$ (Ground Polished Stainless)




Fig. 24

Boiler Shell Stress No Fluid Loading

5 foot Diameter: 0.015 inch Wall Thickness Stainless Steel




Fig. 25

Boiler Shell Stress With Fluid Loading

5 foot Diameter: 0.015 inch Wall Thickness Stainless Steel
0.07 inch Water Fluid Thickness




Fig. 26

Boiler Shell Cumulative Area & Weight

2.3 foot Fan Hole; 4 foot Long, 0.75 inch Shell Separation
0.015 inch Shell Thickness




Fig. 27

Energy Usage per Output Pound Water

Assuming 100% Compressor & Motor Efficiency




Fig. 28

Energy Usage per Output Pound Water

Assuming 100% Compressor & Motor Efficiency




Fig. 29

System Energy Efficiency

Specific Energy Computed at 70 °F Boiler Temperature




Fig. 30

Seawater Boiling Point Rise

Variable Salinity Concentrations




Fig. 31




Fig. 32

Seawater Boiling Point Rise

Variable Salinity Concentrations




Fig. 31




Fig. 32